
Django redis admin Documentation

Release 0.3.0

Rick van Hattem (Wolph)

Aug 29, 2023

Contents

1	Django Redis Admin	3
1.1	Introduction	3
1.2	Requirements	3
1.3	Installation	3
1.3.1	Basic configuration	4
1.3.2	Explicit configuration	4
1.3.3	Master slave configuration	4
1.3.4	Sentinel Configuration	4
1.3.5	Base64 and/or JSON decoding	5
1.3.6	Representation cropping	5
1.4	TODO	5
2	redis_admin package	7
2.1	Submodules	7
2.2	redis_admin.settings module	7
2.3	redis_admin.client module	7
2.4	redis_admin.models module	8
2.5	redis_admin.admin module	11
3	Indices and tables	13
	Python Module Index	15
	Index	17

Source: <https://github.com/WoLpH/django-redis-admin>

Contents:

1.1 Introduction

With *django-redis-admin* you can view (and in the future, edit) your Redis databases. It supports simple servers, master slave setups and sentinel setups.

The admin works by creating a *RedisQueryset* which fakes Django models and querysets so the *ModelAdmin* thinks it's using a regular database backed model.

Since Redis only supports basic types the library allows for optional *base64* encoding/decoding and *json* encoding/decoding.

While I would not recommend using it as a regular queryset to access Redis. In addition to querying data it does some extra queries which you usually don't need (such as fetching idle data) and it does some automatic conversion steps.

1.2 Requirements

- Python 3.6 and above
- Django (tested with 2.1, probably works with any version that supports Python 3)
- Python-redis (*pip install redis*)

1.3 Installation

django-redis-admin can be installed via pip.

```
pip install django-redis-admin
```

Then just add *redis_admin* to your *INSTALLED_APPS*.

Optionally, configure your servers if you have multiple and/or non-standard (i.e. non-localhost) redis servers.

Below are several example configurations. The default settings can always be found in `redis_admin/settings.py`

You can run the demo project using the following commands:

```
cd test_redis_admin
python manage.py runserver
```

The default username/password is `admin/admin`: `http://localhost:8080/admin/`

1.3.1 Basic configuration

```
# https://redis-py.readthedocs.io/en/latest/index.html#redis.Redis
REDIS_SERVERS = dict(
    localhost=dict(),
)
```

1.3.2 Explicit configuration

```
# https://redis-py.readthedocs.io/en/latest/index.html#redis.Redis
REDIS_SERVERS = dict(
    redis_server_a=dict(host='127.0.0.1', port=6379, db=0),
)
```

1.3.3 Master slave configuration

```
# https://redis-py.readthedocs.io/en/latest/index.html#redis.Redis
REDIS_SERVERS = dict(
    redis_server_a=dict(
        master=dict(host='master_hostname', port=6379, db=0),
        slave=dict(host='slave_hostname', port=6379, db=0),
    )
)
```

1.3.4 Sentinel Configuration

```
# The `REDIS_SENTINELS` setting should be a list containing host/port
# combinations. As documented here:
# https://github.com/andymccurdy/redis-py/blob/master/README.rst#sentinel-support
REDIS_SENTINELS = [('server_a', 26379), ('server_b', 26379)]

# The `REDIS_SENTINEL_OPTIONS` are the extra arguments to
# `redis.sentinel.Sentinel`:
# https://github.com/andymccurdy/redis-py/blob/
# cdf2befbe00db4a3c48c9ddd6d64dea15f6f0db/redis/sentinel.py#L128-L155
REDIS_SENTINEL_OPTIONS = dict(socket_timeout=0.1)

# The `service_name` is used to find the server within the Sentinel
# configuration. The dictionary key will be used as the name in the admin
# https://redis-py.readthedocs.io/en/latest/index.html#redis.Redis
REDIS_SERVERS = dict(
```

(continues on next page)

(continued from previous page)

```
name_in_admin=dict(service_name='name_in_sentinel'),
other_server=dict(service_name='other_server'),
)
```

1.3.5 Base64 and/or JSON decoding

As a convenient option all values can optionally be *base64* and/or *json* encoded. To configure this a regular expression can be specified which will be matched against the keys.

```
# For all keys
REDIS_JSON_KEY_RE = '.*'
REDIS_BASE64_KEY_RE = '.*'

# Keys starting with a pattern:
REDIS_BASE64_KEY_RE = '^some_prefix.*'

# Keys ending with a pattern:
REDIS_JSON_KEY_RE = '.*some_suffix$'
```

And if a specific *json* decoder is needed, the *json* module can be specified. The module needs to be importable and have a *dumps* and *loads* method. By default it simply imports the *json* module:

```
REDIS_JSON_MODULE = 'json'
```

1.3.6 Representation cropping

Within the Django Admin list view the values are cropped by default to prevent really long lines. This size can be adjusted through:

```
REDIS_REPR_CROP_SIZE = 150
```

1.4 TODO

- Allow saving values
- Allow deleting values
- Support Redis Bitmaps
- Support Redis HyperLogLogs

2.1 Submodules

2.2 redis_admin.settings module

`redis_admin.settings.CROP_SIZE = 150`

The maximum amount of characters to show before cropping them in the admin list view

`redis_admin.settings.JSON_MODULE = <module 'json' from '/home/docs/.pyenv/versions/3.7.9/lib/python3.7/json.py'>`

Can be any importable module that has a *loads* and *dumps* function

`redis_admin.settings.SENTINELS = []`

The *REDIS_SENTINELS* setting should be a list containing host/port combinations. As documented here: <https://github.com/andymccurdy/redis-py/blob/master/README.rst#sentinel-support> For example: `[('server_a', 26379), ('server_b', 26379)]`

`redis_admin.settings.SENTINEL_OPTIONS = {'socket_timeout': 0.3}`

The *REDIS_SENTINEL_OPTIONS* are the extra arguments to *redis.sentinel.Sentinel*: <https://github.com/andymccurdy/redis-py/blob/cdfe2befbe00db4a3c48c9ddd6d64dea15f6f0db/redis/sentinel.py#L128-L155>

`redis_admin.settings.SERVERS = {'default': {}}`

To use a separate *master/slave* configuration *master/slave* sub-dictionaries can be provided. Otherwise the top-level dictionary will be passed along to *redis.Redis*: <https://redis-py.readthedocs.io/en/latest/index.html#redis.Redis>

`redis_admin.settings.SOCKET_TIMEOUT = 0.3`

Default socket timeout if no other settings are given.

2.3 redis_admin.client module

`redis_admin.client.get_master(name) → redis.client.Redis`

`redis_admin.client.get_sentinel()`

`redis_admin.client.get_slave(name)` → `redis.client.Redis`

2.4 redis_admin.models module

```
class redis_admin.models.Default(key, raw_value, type, expires_at, idle_since, base64, json)
    Bases: redis_admin.models.RedisValue

    exception DoesNotExist
        Bases: django.core.exceptions.ObjectDoesNotExist

    exception MultipleObjectsReturned
        Bases: django.core.exceptions.MultipleObjectsReturned

    objects = <django.db.models.manager.Manager object>

class redis_admin.models.Meta
    Bases: redis_admin.models.RedisMeta

class redis_admin.models.RedisHash(key, raw_value, type, expires_at, idle_since, base64, json)
    Bases: redis_admin.models.RedisValue

    exception DoesNotExist
        Bases: django.core.exceptions.ObjectDoesNotExist

    exception MultipleObjectsReturned
        Bases: django.core.exceptions.MultipleObjectsReturned

    fetch_value (client: redis.client.Redis)
        Fetch the value. Note that if a pipe is passed as client the result will be in the pipe.execute() instead

    objects = <django.db.models.manager.Manager object>

rediszset
    Accessor to the related object on the reverse side of a one-to-one relation.

    In the example:



```
class Restaurant(Model):
 place = OneToOneField(Place, related_name='restaurant')
```

Place.restaurant is a ReverseOneToOneDescriptor instance.

value

class redis_admin.models.RedisList(key, raw_value, type, expires_at, idle_since, base64, json)
    Bases: redis_admin.models.RedisValue

    exception DoesNotExist
        Bases: django.core.exceptions.ObjectDoesNotExist

    exception MultipleObjectsReturned
        Bases: django.core.exceptions.MultipleObjectsReturned

    fetch_value (client: redis.client.Redis)
        Fetch the value. Note that if a pipe is passed as client the result will be in the pipe.execute() instead

    objects = <django.db.models.manager.Manager object>

redisset
    Accessor to the related object on the reverse side of a one-to-one relation.

    In the example:
```

```
class Restaurant(Model):
    place = OneToOneField(Place, related_name='restaurant')
```

Place.restaurant is a ReverseOneToOneDescriptor instance.

value

```
class redis_admin.models.RedisMeta
```

Bases: object

get_field(name)

managed = False

```
class redis_admin.models.RedisSet(key, raw_value, type, expires_at, idle_since, base64, json,
                                  redislist_ptr)
```

Bases: redis_admin.models.RedisList

exception DoesNotExist

Bases: redis_admin.models.DoesNotExist

exception MultipleObjectsReturned

Bases: redis_admin.models.MultipleObjectsReturned

fetch_value(client: redis.client.Redis)

Fetch the value. Note that if a pipe is passed as *client* the result will be in the *pipe.execute()* instead

redislist_ptr

Accessor to the related object on the forward side of a one-to-one relation.

In the example:

```
class Restaurant(Model):
    place = OneToOneField(Place, related_name='restaurant')
```

Restaurant.place is a ForwardOneToOneDescriptor instance.

redislist_ptr_id

value

```
class redis_admin.models.RedisString(key, raw_value, type, expires_at, idle_since, base64,
                                     json)
```

Bases: redis_admin.models.RedisValue

exception DoesNotExist

Bases: django.core.exceptions.ObjectDoesNotExist

exception MultipleObjectsReturned

Bases: django.core.exceptions.MultipleObjectsReturned

fetch_value(client: redis.client.Redis)

Fetch the value. Note that if a pipe is passed as *client* the result will be in the *pipe.execute()* instead

objects = <django.db.models.manager.Manager object>

value

```
class redis_admin.models.RedisValue(*args, **kwargs)
```

Bases: django.db.models.base.Model

class Meta

Bases: redis_admin.models.RedisMeta

abstract = False

```
TYPES = {'hash': <class 'redis_admin.models.RedisHash'>, 'list': <class 'redis_admin
```

base64
A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

classmethod create (*type*, ***kwargs*)

cropped_value

decode_string (*raw_value*)

expires_at
A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

fetch_value (*client: redis.client.Redis*)
Fetch the value. Note that if a pipe is passed as *client* the result will be in the *pipe.execute()* instead

get_cropped_value (*crop_size*)

idle

idle_since
A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

json
A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

key
A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

raw_value
A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

classmethod register_type (*type*)

ttl

type
A wrapper for a deferred-loading field. When the value is read from this object the first time, the query is executed.

value

```
class redis_admin.models.RedisZSet (key, raw_value, type, expires_at, idle_since, base64, json,
                                   redishash_ptr)
    Bases: redis_admin.models.RedisHash

    exception DoesNotExist
        Bases: redis_admin.models.DoesNotExist

    exception MultipleObjectsReturned
        Bases: redis_admin.models.MultipleObjectsReturned

    fetch_value (client: redis.client.Redis)
        Fetch the value. Note that if a pipe is passed as client the result will be in the pipe.execute() instead

    redishash_ptr
        Accessor to the related object on the forward side of a one-to-one relation.
```

In the example:

```
class Restaurant(Model):
    place = OneToOneField(Place, related_name='restaurant')
```

`Restaurant.place` is a `ForwardOneToOneDescriptor` instance.

redishash_ptr_id

value

`redis_admin.models.decode_bytes(value, encoding='utf-8', method='replace')`

2.5 redis_admin.admin module

```
class redis_admin.admin.Query(queryset)
```

Bases: `object`

order_by = ()

select_related(*args, **kwargs)

```
class redis_admin.admin.Queryset(model: redis_admin.models.RedisValue, slice_limit=101)
```

Bases: `object`

count()

filter(*filters, **raw_filters)

get(*args, **kwargs)

order_by(*args, **kwargs)

```
class redis_admin.admin.RedisAdmin(model, admin_site)
```

Bases: `django.contrib.admin.options.ModelAdmin`

get_queryset(request)

Return a `QuerySet` of all model instances that can be edited by the admin site. This is used by `change-list-view`.

list_display = ['key', 'type', 'expires_at', 'ttl', 'idle', 'cropped_value', 'json', '']

media

readonly_fields = ['key', 'raw_value', 'type', 'expires_at', 'idle_since', 'base64', '']

search_fields = ('key__contains',)

show_full_result_count = False

`redis_admin.admin.grouper(iterable, n, fillvalue=None)`

CHAPTER 3

Indices and tables

- `genindex`
- `modindex`
- `search`

r

- `redis_admin.admin`, [11](#)
- `redis_admin.client`, [7](#)
- `redis_admin.models`, [8](#)
- `redis_admin.settings`, [7](#)

A

abstract (*redis_admin.models.RedisValue.Meta* attribute), 9

B

base64 (*redis_admin.models.RedisValue* attribute), 10

C

count() (*redis_admin.admin.Queryset* method), 11

create() (*redis_admin.models.RedisValue* class method), 10

CROP_SIZE (in module *redis_admin.settings*), 7

cropped_value (*redis_admin.models.RedisValue* attribute), 10

D

decode_bytes() (in module *redis_admin.models*), 11

decode_string() (*redis_admin.models.RedisValue* method), 10

Default (class in *redis_admin.models*), 8

Default.DoesNotExist, 8

Default.MultipleObjectsReturned, 8

E

expires_at (*redis_admin.models.RedisValue* attribute), 10

F

fetch_value() (*redis_admin.models.RedisHash* method), 8

fetch_value() (*redis_admin.models.RedisList* method), 8

fetch_value() (*redis_admin.models.RedisSet* method), 9

fetch_value() (*redis_admin.models.RedisString* method), 9

fetch_value() (*redis_admin.models.RedisValue* method), 10

fetch_value() (*redis_admin.models.RedisZSet* method), 10

filter() (*redis_admin.admin.Queryset* method), 11

G

get() (*redis_admin.admin.Queryset* method), 11

get_cropped_value() (*redis_admin.models.RedisValue* method), 10

get_field() (*redis_admin.models.RedisMeta* method), 9

get_master() (in module *redis_admin.client*), 7

get_queryset() (*redis_admin.admin.RedisAdmin* method), 11

get_sentinel() (in module *redis_admin.client*), 7

get_slave() (in module *redis_admin.client*), 7

groupby() (in module *redis_admin.admin*), 11

I

idle (*redis_admin.models.RedisValue* attribute), 10

idle_since (*redis_admin.models.RedisValue* attribute), 10

J

json (*redis_admin.models.RedisValue* attribute), 10

JSON_MODULE (in module *redis_admin.settings*), 7

K

key (*redis_admin.models.RedisValue* attribute), 10

L

list_display (*redis_admin.admin.RedisAdmin* attribute), 11

M

managed (*redis_admin.models.RedisMeta* attribute), 9

media (*redis_admin.admin.RedisAdmin* attribute), 11

Meta (class in *redis_admin.models*), 8

O

objects (*redis_admin.models.Default* attribute), 8

objects (*redis_admin.models.RedisHash* attribute), 8
objects (*redis_admin.models.RedisList* attribute), 8
objects (*redis_admin.models.RedisString* attribute), 9
order_by (*redis_admin.admin.Query* attribute), 11
order_by() (*redis_admin.admin.Queryset* method), 11

Q

Query (*class in redis_admin.admin*), 11
Queryset (*class in redis_admin.admin*), 11

R

raw_value (*redis_admin.models.RedisValue* attribute), 10
readonly_fields (*redis_admin.admin.RedisAdmin* attribute), 11
redis_admin.admin (*module*), 11
redis_admin.client (*module*), 7
redis_admin.models (*module*), 8
redis_admin.settings (*module*), 7
RedisAdmin (*class in redis_admin.admin*), 11
RedisHash (*class in redis_admin.models*), 8
RedisHash.DoesNotExist, 8
RedisHash.MultipleObjectsReturned, 8
redishash_ptr (*redis_admin.models.RedisZSet* attribute), 10
redishash_ptr_id (*redis_admin.models.RedisZSet* attribute), 11
RedisList (*class in redis_admin.models*), 8
RedisList.DoesNotExist, 8
RedisList.MultipleObjectsReturned, 8
redislist_ptr (*redis_admin.models.RedisSet* attribute), 9
redislist_ptr_id (*redis_admin.models.RedisSet* attribute), 9
RedisMeta (*class in redis_admin.models*), 9
RedisSet (*class in redis_admin.models*), 9
redisset (*redis_admin.models.RedisList* attribute), 8
RedisSet.DoesNotExist, 9
RedisSet.MultipleObjectsReturned, 9
RedisString (*class in redis_admin.models*), 9
RedisString.DoesNotExist, 9
RedisString.MultipleObjectsReturned, 9
RedisValue (*class in redis_admin.models*), 9
RedisValue.Meta (*class in redis_admin.models*), 9
RedisZSet (*class in redis_admin.models*), 10
rediszset (*redis_admin.models.RedisHash* attribute), 8
RedisZSet.DoesNotExist, 10
RedisZSet.MultipleObjectsReturned, 10
register_type() (*redis_admin.models.RedisValue* class method), 10

S

search_fields (*redis_admin.admin.RedisAdmin* attribute), 11
select_related() (*redis_admin.admin.Query* method), 11
SENTINEL_OPTIONS (*in module redis_admin.settings*), 7
SENTINELS (*in module redis_admin.settings*), 7
SERVERS (*in module redis_admin.settings*), 7
show_full_result_count (*redis_admin.admin.RedisAdmin* attribute), 11
SOCKET_TIMEOUT (*in module redis_admin.settings*), 7

T

ttl (*redis_admin.models.RedisValue* attribute), 10
type (*redis_admin.models.RedisValue* attribute), 10
TYPES (*redis_admin.models.RedisValue* attribute), 9

V

value (*redis_admin.models.RedisHash* attribute), 8
value (*redis_admin.models.RedisList* attribute), 9
value (*redis_admin.models.RedisSet* attribute), 9
value (*redis_admin.models.RedisString* attribute), 9
value (*redis_admin.models.RedisValue* attribute), 10
value (*redis_admin.models.RedisZSet* attribute), 11